



An all-round exterior wood product

MicroPro® preservative technology is the most advanced wood treatment process for wood used in decks, fences, landscaping and general exterior construction uses. MicroPro preservative technology meets Canadian Standards Association (CSA) standards as a wood preservative that has been formulated especially for Canadian species and use conditions. MicroPro Sienna Treated Wood can be used in residential applications above ground, in ground contact and in freshwater contact. Usage is indicated on the end tag attached to the treated lumber.

MicroPro Sienna is no more corrosive to metal products than untreated wood. Fasteners and hardware should be rated to the environment and conform to building codes. Aluminum building products may be placed in direct contact with MicroPro Sienna Treated Wood used indoors or in above ground exterior applications where the wood is not exposed to frequent and prolonged wetting, such as decks and fencing. (For more information, see the Fastener and Hardware Information sheet online.)

MicroPro Sienna Treated Wood products produced and used in Canada are backed by the MicroPro Sienna Residential Limited Warranty for first owners against structural failure caused by fungal decay or termites. (See warranty literature online for details.)

A positive choice for an eco-lifestyle

MicroPro Sienna Treated Wood is processed using patented MicroPro micronized copper preservative. This technology reduces the environmental footprint of Sienna to less than half that of traditional residential treated wood.


- The MicroPro treated wood process was the first, and is the only, wood treatment process to be certified as an Environmentally Preferable Product (EPP) by Scientific Certification Systems (SCS), based on Life-Cycle Assessment.
- UL GREENGUARD GOLD Certification indicates that MicroPro preservative technology has undergone rigorous testing and has met stringent standards for low volatile organic compound (VOC) emissions. Products certified to this criteria are suitable for use in schools, offices, and other sensitive environments.
- Wood products treated with MicroPro technology are eligible for more green building points toward NGBS Green Certification than any other treated wood.



An attractive design alternative

MicroPro Sienna Treated Wood uses innovative micronized pigment technology to give the wood a warm natural brown tone that enhances its grain and natural characteristics. It offers a rich, finished look that complements today's deck furniture and furnishings.

Natural colour variations in the product are to be expected due to varying exposure conditions and the variation between different species of wood. In addition, colour variations may occur between heartwood and sapwood and knot areas from board to board or within the same piece of wood. We recommend that you make your selection of MicroPro Sienna product from actual samples of the wood and that you inspect the product prior to installation for colour and other natural variations in the product.



It is possible that on some MicroPro Sienna Treated Wood a green colour may appear along the grain of the wood and around knots. Over time the green colour will soften and blend into the overall tone of the wood.

A colour-matched sealer for pressure treated wood, Cut-N-Seal® is available to cover cuts and holes above ground and to retouch any blemishes during construction of the project.

In an exterior project, the colour of MicroPro Sienna will turn to warm tan and over time will gradually transition to driftwood grey. The length of time will vary according to the exposure to sunlight, the wood species and the application. Long term, the initial colour will provide a good foundation for staining to renew or change the colour.

To maintain the colour and surface of MicroPro Sienna Treated Wood a high quality water repellent or semi-transparent stain should be applied to the wood as soon as possible after construction of the project.

Unless the coating manufacturer stipulates otherwise, you can apply a stain or water repellent to the wood as soon as it is dry to the touch, which may be as soon as two weeks or as long as eight or more. It will depend on the weather, the exposure to sunlight and how wet the wood was when it was installed (it is saturated with water during pressure treatment). To test that the treated wood is surface dry, sprinkle water droplets on the surface. If the water droplets are absorbed into the wood, it is ready for stain. If not, try sprinkling again in a few days. Always read the finish product label and follow the manufacturer's recommendations on how and when the product should be applied.



Important Information

MicroPro Sienna® Treated Wood products are pressure treated with MicroPro® Micronized Copper Azole (MCA) to protect the wood against fungal decay and termite attack. The main ingredient in the preservative system is copper, which has long been known as an effective wood preservative. MicroPro Sienna uses micronized copper coupled with micronized azole for long-term protection of wood exposed in exterior applications.

- Do not burn treated wood.
- Wear a dust mask and goggles when cutting or sanding wood.
- Wear gloves when working with wood.
- Some preservative and/or pigment colour may migrate from the treated wood into soil, water and other surfaces. It may also dislodge from the treated wood surface upon contact with skin. Wash exposed skin areas thoroughly.
- All sawdust and construction debris should be cleaned up and disposed of after construction.
- Wash work clothes separately from other household clothing before reuse.
- Treated wood should not be used where it may come into direct or indirect contact with drinking water, except for uses involving incidental contact such as freshwater docks and bridges.
- Do not use treated wood under circumstances where the preservative may become a component of food, animal feed, or beehives.
- Do not use treated wood as mulch.
- Only treated wood that is visibly clean and free of surface residue should be used.
- If the wood is to be used in an interior application and becomes wet during construction, it should be allowed to dry before being covered or enclosed.
- Projects should be designed and installed in accordance with federal, provincial, and local building codes and ordinances governing construction in your area.
- Users should dispose of treated wood scraps and cut offs in accordance with local, provincial and federal regulations.
- Use wood preservative safely. Always read the label and product information before use.

Important Application Information

Cut ends / Field cuts – When building your outdoor project with pressure treated wood it is important to protect the cut ends, drill holes, and other field cuts.

- For pressure treated wood is used in **ground contact applications**, two applications of a brush-on copper naphthenate based end-cut wood preservative must be applied to all saw cuts, drill holes and other field cuts at the time of construction before the wood is installed. Follow the manufacturer's directions for proper application.
- For pressure treated wood used in **above ground applications**, such as deck boards, railings, post tops or fence boards, a brush-on end-cut wood preservative or Timber Specialties Cut-N-Seal® product should be applied to all saw cuts, drill holes and other field cuts at the time of construction. Follow the manufacturer's directions for proper application.

Fasteners – Wood treated with MicroPro technology exhibits corrosion rates on metal products similar to untreated wood. Use fasteners and hardware designed for exterior construction that are in compliance with the manufacturer's recommendations and the building codes for their intended use. For more information, see the *Fastener and Hardware Information* sheet online.

Contact with aluminum – Aluminum building products may be placed in direct contact with MicroPro Sienna Treated Wood products used for interior uses and above ground exterior applications where the wood is not exposed to frequent and prolonged wetting, such as decks and fencing. MicroPro Sienna Treated Wood in direct contact with aluminum products should only be used in code compliant construction applications that provide proper water drainage and do not allow the wood to be exposed to, or remain in contact with a continual moisture source, standing water or water immersion, such as boat docks, hot tubs and swimming pools. In addition, MicroPro Sienna Treated Wood should not be encased, sealed, or wrapped with aluminum products where moisture or water can be trapped, so as to avoid pitting or other undesirable results. For more information, see the *Fastener and Hardware Information* sheet online.

Appropriate usage – Above Ground treated wood should not be used in ground contact applications, as this can adversely affect the performance of the entire project. The appropriate usage is noted on the end tag attached to each piece of MicroPro Sienna Treated Wood.

Pilot holes – Drill pilot holes to minimize splitting especially when nailing or screwing near the edge or end of a board.

Mold growth – Mold growth can and does occur on the surface of many products, including untreated and treated wood, during prolonged surface exposure to excessive moisture conditions. To remove mold from the treated wood surface, wood should be allowed to dry. Typically, mild soap and water can be used to remove remaining surface mold.

For more information, visit www.MicroProSienna.com.

© 2018

Actual product colour may vary from colour shown in photos.

MicroPro Sienna Treated Wood products are produced by independently owned and operated wood preserving facilities.

MicroPro, MicroPro Sienna and Cut-N-Seal are registered trademarks of Koppers Performance Chemicals Inc.